

EMINERE™ 1 / 2 / 3 / 4

Eminere was designed by Anolis for a wide range of exterior and interior applications with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. Equipped with Anolis' unique 18-bit colour mixing resolution ensures extra fine colour tuning as well as smooth dimming at low level of intensity. Designed in our state of the art R&D facility by industry experts with over 10 years experience in their field, Eminere is IP67 rated and can withstand extreme conditions. Eminere is available in 1, 2, 3, and 4 foot sizes (300/600/900/1200 mm) with RGBW, RGBA or PureWhite single chips as standard and is easy to control, 1 pixel per foot. Eminere fixtures can be used for both permanent and temporary installations, including various architectural and architectural applications.



KEY FEATURES

Application Flexibility

Eminere's optics can be used for various applications including wall grazing, flood lighting, wall washing, wide flood lighting, spot lighting and accent lighting.

Quick and Easy Installation

Plug & Play system means easy installation, fast adjustment and intuitive programming with self-addressing.

Naturally looking result

Full spectrum coverage by using RGBW colour mixing with precise wave lengths of each colour for modern architecture or specifically designed combination of RGBA to highlight every single detail of historical buildings or monuments. Output up to 1.147 lm (RGBW) or 1.652 lm (PW) per one foot of Eminere.

Durability

Eminere is rated IP67, suitable for wet locations and has a protection rating of IK06. Marine grade finish option also available for harsh environmental conditions.


COLOURS



CONTROL & PROTOCOLS




STANDARD & SPECIFICATION



FINISH OPTIONS




COLOUR TEMPERATURE




OPTIC OPTIONS

SYMMETRICAL



BI-SYMMETRICAL




ASYMMETRICAL



EMINERE SPECIFICATION

ELECTRICAL	Input Voltage	120 - 277 V AC 50/60 Hz		
	Typical Power Consumption	Eminere 1 / 2 / 3 / 4 : 25 W / 45 W / 65 W / 85 W		
OPTICAL	Light Source	Eminere 1 / 2 / 3 / 4 : 12, 24, 36, 48 x High Power Single Chip LEDs		
	Colour Variants	RGBW (W - 6.500 K)		PW (W - 3.000 K)
		Variants On Request: TW (2700 - 6500 K) 2.200 K 2.500 K 2.700 K 3.500 K 4.000 K 5.000 K 6.500 K		
	Beam Angle	Symmetrical:	9° 15° 30° 50° 65° 100°	
		Bi-symmetrical:	10°x30° 30°x10° 10°x60° 60°x10° 35°x70° 70°x35° 15°x90° 90°x15°	
		Asymmetrical:	Wallwasher Wide Wallwasher	
	Lumen Output Delivered	Eminere 1: 1.147 lm, RGBW @ 9°		Eminere 3: 3.441 lm, RGBW @ 9°
		Eminere 2: 2.294 lm, RGBW @ 9°		Eminere 4: 4.588 lm, RGBW @ 9°
	Projected Lumen Maintenance	60.000 hrs (L70 @ 25 °C / 77 °F)		
	CONTROL	Interface Protocol	Via E-Box range or Wireless DMX (excluded Eminere 1)	
E-Box Control Protocols		USITT DMX512, RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net		
Wireless DMX (Option)		Lumen Radio CRMX Technology		
Operating Modes		Pixel (12 LEDs/300mm) or Fixture mode		
Setting / Addressing		Via Two Row LCD Display with Control Buttons or RDM communicator		
Power Supply		Integrated		
Connectivity		E-box Lite	144 of Eminere 1 (@ 230 V and 40m cable) via 1 Output	
	E-box Daisy	144 of Eminere 1 (@ 230 V and 40m cable) via 1 Output		
	E-box Star	144 of Eminere 1 (@ 230 V and 40m cable) via 6 Outputs		
PHYSICAL	Width x Height x Length	Eminere 1 / 2 / 3 / 4	76 x 107 x 329 / 629 / 929 / 1229 mm 2.99 x 3.58 x 12.95 / 24.76 / 36.57 / 48.38 in.	
	Weight	2.5 kg 5.5 lbs	4.0 kg 8.82 lbs	6.02 kg 13.27 lbs 7.7 kg 17.0 lbs
	Housing	High Pressure Extruded Aluminium Body End Caps - Die-Cast Aluminium Tempered Glass		
	Finish Options	Standard Colour	Graphite Black (RAL 9011) Silver (RAL 9006)	
		Cost Option	Custom RAL Harsh Environment (RAL 9016, RAL 9011)	
	Cables / Connections	IP67 Hybrid Connection (Power + Data)		
	Mounting Method	Surface Mount With Different Type of Brackets		
	Adjustability	+/- 95°		
	Protection Factor	IP67 / Suitable For Wet Locations		
	IK Rating	IK06		
	Cooling System	Convection		
	Operating Ambient Temperature	-20 °C / +40 °C (-4 °F / +104 °F)		
	Operating Temperature	+67 °C @ Ambient +40 °C (+153 °F @ Ambient +104 °F)		
	CERTIFICATION	Listings	ETL / cETL, CE, RoHS, UKCA	
	ACCESSORIES	Mounting Brackets	Mounting Brackets 50 100 200 300 mm custom length	
Cable Covers		Cable Cover For Eminere 1 2 3 4		
Shields		Shield For Eminere 1 2 3 4		
Optical Demo Set		Optical Demo Set For Eminere 1 2 3 4		
Cables and Connectors		Field Installable Connector FF		Field Installable Connector FM
		Cable CE WCA		Cable US WCA
		Waterproof Cover Cap FM ZAHB-0006		
		CE/UL Leader Cables FF for Eminere:		Leader Cable FF 2 5 10 25 50 m
		CE/UL Jumper Cables FF/FM for Eminere:		Jumper Cable FF/FM 0,25 0,5 1 2 3 5 10 m
Booster Box		Booster Box		

DIMENSIONS



PROJECTED AREA

	Front (rear) - m²	Front (rear) ft²	Side - m²	Side - ft²	Top - m²	Top - ft²
Eminere 1 with Shield with cable cover	0,028 0,049 0,032	0,301 0,527 0,344	0,007 - -	0,075 - -	0,025 0,026 0,026	0,269 0,280 0,280
Eminere 2 with Shield with cable cover	0,045 0,093 0,060	0,484 1,001 0,646	0,007 - -	0,075 - -	0,048 0,049 0,049	0,516 0,527 0,527
Eminere 3 with Shield with cable cover	0,072 0,135 0,087	0,775 1,452 0,936	0,007 - -	0,075 - -	0,071 0,073 0,073	0,764 0,785 0,785
Eminere 4 with Shield with cable cover	0,100 0,178 0,115	1,076 1,915 1,237	0,007 - -	0,075 - -	0,094 0,096 0,096	1,011 1,033 1,033


PHOTOMETRIC OVERVIEW

Based on RGBW version, all leds @ full


Lumen Output (lm)				
	EMINERE 1	EMINERE 2	EMINERE 3	EMINERE 4
9°	1147	2 294	3 441	4 588
15°	978	1 956	2 910	3 912
30°	1 046	2 092	3 138	4 184
50°	1 039	2 078	3 117	4 156
65°	1 040	2 080	3 120	4 160
100°	996	1 992	2 988	3 984
10° x 30°	1 032	2 064	3 096	4 128
10° x 60°	1 051	1 874	2 811	3 748
15° x 90°	970	1 940	2 934	3 880
35° x 70°	1 040	2 080	3 120	4 160
WallWasher	952	1 904	2 856	3 806
Wide WallWasher	854	1 708	2 562	3 416

BI-SYMMETRICAL BEAM ANGLES

Bi-symmetrical: 10°x30°, 10°x60°, 35°x70°, 15°x90°




Bi-symmetrical: 30°x10°, 60°x10°, 70°x35°, 90°x15°



EMINERE WALLWASHER INPUT OPTIONS

STANDARD


UPON REQUEST



COLOUR MIXING PRINTS


STAND ALONE Specially designed glass printing to achieve optimal colour mixing and intensity distribution.

HEAD2HEAD Fixtures without special end glass print installed right next to each other create absolutely perfect colour and intensity overlap.




HEAD2HEAD

SYMMETRICAL




STAND ALONE



HEAD2HEAD

WALLWASHER



STAND ALONE

Note: Applies for RGBW, RGBA versions. Pure white and Tunable white versions are always without the end print (no matter on their position to other fixture).

E-BOX SPECIFICATION


ELECTRICAL	Input Voltage	120 – 277 V AC 50/60 Hz		
	Wireless DMX (Option)	Lumen Radio CRMX Technology		
CONTROL	Interface Protocol	E-box Lite: USITT DMX512, RDM		
		E-box Daisy / Star: USITT DMX512, RDM, ArtNet, MA Net, MA Net2, sACN, Kling-Net		
	Operating Modes	E-box Lite / Daisy: Fixture Mode, Pixel Mode, Output Mode		
		E-Box Star: Total Mode, Fixture Mode, Pixel Mode, Output Mode		
	Display	Via Two Row LCD Display with Control Buttons or RDM communicator		
	Control System	E-box With Self Addressing Feature or Custom Setting Via LCD Display/RDM		
	Power Supply	Integrated		
	Connectivity	E-box Lite	144 of Eminere 1 (@ 230 V and 40m cable) via 1 Output	
PHYSICAL		E-box Daisy	144 of Eminere 1 (@ 230 V and 40m cable) via 1 Output	
		E-box Star	144 of Eminere 1 (@ 230 V and 40m cable) via 6 Outputs	
	Length x Width x Height	E-box Lite	220 x 120 x 81 mm (8.66 x 4.72 x 3.18 in.)	
		E-box Daisy	260 x 160 x 91 mm (10.24 x 6.30 x 3.58 in.)	
		E-box Star	280 x 230 x 111 mm (11.02 x 9.06 x 4.37 in.)	
	Weight	1.67 kg 3.85 lbs	2.78 kg 6.13 lbs	4.4 kg 9.7 lbs
	Housing	Die-Cast Aluminium Case		
	Finish Options	Standard Colour - Graphite Black (RAL 9011) Silver (RAL 9006)		
		Cost Option - Custom RAL Harsh Environment (RAL 9016, RAL 9011)		
CERTIFICATION	Cables / Connections	Cable Grommet (stainless steel)		
	Mounting Method	Surface Mount , 4 Mounting Holes		
	Protection Factor	IP67 / Suitable For Wet Locations		
	IK Rating	IK10		
	Cooling System	Convection		
	Operating Ambient Temperature	-20 °C / +40 °C (-4 °F / +104 °F)		
	Listings	ETL / cETL, CE, RoHS, UKCA		

COMPARISON


	E-BOX LITE	E-BOX DAISY	E-BOX STAR
Power input	1	1	1
Fixture Output	1	1	6
Total load (current)	16A	16A	16A
DMX control	YES	YES	YES
RDM	YES	YES	YES
Art-Net	NO	YES	YES
Ethernet switch	NO	YES	YES
Kling-Net	NO	YES	YES
sACN	NO	YES	YES
MA Net, MA Net2	NO	YES	YES

E-BOX DIMENSIONS


E-BOX LITE



E-BOX DAISY



E-BOX STAR




CONNECTIVITY

Following table shows maximum connected Emineres on each output of E-Box with respect of cable length.


Cable length (m)		Voltage (V)					Cable length (m)		Voltage (V)				
		100	120	190	230	277			100	120	190	230	277
EMINERE 1	10	69	83	131	159	191	EMINERE 3	10	23	28	44	53	64
	20	61	83	131	159	191		20	20	28	44	53	64
	30	40	58	131	159	191		30	13	19	44	53	64
	50	24	35	88	128	186		50	8	12	29	43	62
	70	17	25	63	92	133		70	6	8	21	31	44
	100	12	17	44	64	93		100	4	6	15	21	31
	200	6	9	22	32	47		200	2	3	7	11	16
EMINERE 2	10	34	41	64	78	94	EMINERE 4	10	17	21	33	40	48
	20	30	41	64	78	94		20	15	21	33	40	48
	30	20	28	64	78	94		30	10	15	33	40	48
	50	12	17	43	63	91		50	6	9	22	32	47
	70	8	12	31	45	65		70	4	6	16	23	38
	100	6	9	21	31	46		100	3	4	11	16	23
	200	3	4	11	16	23		200	2	2	5	8	12

* Cable length is a total cable length between E-box and last connected Eminere. Example: Total cable length=L1+L2+L3




CONNECTION

E-BOX LITE / DAISY





E-BOX STAR




CONNECTION - WIRELESS VERSION

Connection setup, where every Eminere is independently accepting data from WIFI.




THE BOOSTER BOX


To compensate a voltage drop in a large installation, the Booster boxes have to be connected in the chain of Eminere modules.



Example: E-box Daisy, Power supply= 230V, Cable length=70m, fixture=Eminere 2.
The Booster box has to be connected after every 45th Eminere 2 (fixture 45 and fixture 90) from 94 fixtures.



DIMENSIONS




BOOSTER BOX POSITIONS

		Max. number of Emineres 1 = 191 (in Standard mode)			
		120 V	190 V	230 V	277 V
EMINERE 1	10 m	83,166	131	159	-
	20 m	83,166	131	159	-
	30 m	58,116,174	131	159	-
	50 m	35,70,105,140,175	88,176	128	186
	70 m	25,50,75,100,125,150,175	63,126,189	92,184	133
	100 m	17,34,51,68,85,102,119,136,153,170,187	44,88,132,176	64,128	93,186
	200 m	9,18,27,36,45,54,60,72,81,90,99,108,117,126,135,144, 153,162,171,180,189,	22,44,66,88,110,132,154,176	32,64,96,128,	47,94,141,188


NOTE: For more detail see the User manual.

ACCESSORIES


Cable Cover for Eminere




Shield for Eminere




Optical Demo Set



Mounting brackets



Ceiling Adaptor for Eminere 1 / 2 - custom option



NOTE: This option requires possibility to connect cables to the fixture above a false ceiling. For other connection options please contact the factory.


CABLES

Leader Cable

For connecting E-Box with first Eminere. Comes with Waterproof End Cap which has to be installed to the last Eminere's output connector.

Female connector

Female pins




Jumper Cable

For connection between two Emineres.

NOTE: Custom length of Jumper cable depends on the distance between two Eminere luminaires (length includes cable and connectors).

Female connector

Female pins



Female connector



Male pins

Field installable connector

For special cases, where Jumper Cable can't be used. Then use Leader Cable with Field installable connector to make a connection between Emineres.

Female connector

Female pins




Female connector

Male pins

Output - panel connector
(front view)




Input - panel connector
(front view)



Waterproof End Cap

Install at the end of line to the last Emineres output connector.





Cable lengths available

IN METRES	LEADER CABLE	JUMPER CABLE
0,25	–	YES
0,5	–	YES
1	–	YES
2	YES	YES
3	–	YES



IN METRES	LEADER CABLE	JUMPER CABLE
5	YES	YES
10	YES	YES
25	YES	–
50	YES	–
Other lengths	On Request	

PHOTOMETRIC DATA



Eminere 4 RGBCW 9dg





Eminere 4 RGBCW 15dg





Eminere 4 RGBCW 30dg





Eminere 4 RGBCW 50dg



Eminere 4 RGBCW 65dg




Eminere 4 RGBCW 100dg




PHOTOMETRIC DATA


Eminere 4 RGBCW 10dg x 30dg








Eminere 4 RGBCW 10dg x 60 dg




Eminere 4 RGBCW 35dg x 70dg



Eminere 4 RGBCW 15dg x 90dg



Eminere 4 RGBCW WallWasher



Eminere 4 RGBCW Wide WallWasher

